



Monarch

Renlita Overhead Doors

RENLITA ALUMINIUM DOOR

 A Member of the ARA Group
www.aragroup.com.au

The Renlita all-aluminium counterweight balanced door makes an outstanding statement. A contemporary concept offering luxury, elegance and durability. With no visible welding, the all-aluminium Renlita door offers an exemplary architectural framework. The all-aluminium Renlita door can be produced in either 1000, 2000 or 3000 series.



Applications:

High-end architectural projects or harsh and corrosive environments. All-aluminium Renlita doors come with stainless steel pulleys and hinges as standard.

Features:

The all-aluminium Renlita doorframe is constructed from custom extruded aluminium section, purpose-designed to accept standard glazing. There is no welding on the joints. These are crimped together using triple stakes on corners and purpose made joining spigots to internal members. This provides ideal construction for anodised finishes as there is no discolouration from heat due to welding.

Specifications:

Size - 4500mm wide by 4000mm high. For larger sizes please consult Monarch/Renlita.

Doors can be partially or fully glazed for viewing or showroom display and are glazed in accordance with AS1288. Standard glazing uses 6.38mm laminated safety glass. The use of other glass or glazing material should be referred to the manufacturer due to additional weight, deflection, door design and construction.

Finishes - Doors can be supplied in standard anodised or powder coat finishes.

Locking - By use of internal padbolts. Unless otherwise specified, motorised doors will not be fitted with manual locks.

Counterweight Covers - Counterweights shall be protected and covered with a removable pressed sheet to meet design requirements.

Motorisation - Doors shall be driven by Monarch/Renlita's exclusive patented dual 24 volt DC motor drives operating the linkage and counterweight. Motors are controlled by custom logic control, designed specifically for this operation. Various options for door operation are available including key switch, radio transmitter and card key. Doors have automatic load sensing if an obstruction is detected.

For basic dimensions and clearances please refer to the Monarch / Renlita 1000, 2000 and 3000 specifications.



Monarch / Renlita has a continuous program of product development and reserves the right to change specifications at any time and without notice.

Patent Pending No. 243258



Contact Details

NSW Office

58 Box Road, Taren Point NSW 2229
Phone: (02) 9526 1222 Fax: (02) 9525 1114

QLD Office

56/58 Nestor Drive, Meadowbrook QLD 4131
Phone: (07) 3805 7314 Fax: (07) 3805 7315
QBSA Act Licence No. 1004980

VIC Office

39 Nicholas Drive, Dandenong South VIC 3175
Phone: (03) 9768 2562 Fax: (03) 9768 2563

WA / SA Office

48/110 Inspiration Drive, Wangara WA 6065
Phone: 0414 810 274 Fax: (08) 6210 1508

Visit our website: www.monarchdoors.com.au